

NEW ARCHITECTURAL SLAVE INTERCOM STATIONS

PRELIMINARY RELEASE INFORMATION



Fascia	Polished white plastic	Custom aluminium	Custom timber veneer	Custom mirror finish
Frame	Clear anodised aluminium	Clear anodised aluminium	Custom colour anodised aluminium	Clear anodised aluminium
End caps	Metallised plastic	Black UV stabilised plastic	Metallised plastic	Black UV stabilised plastic
Fasteners	Concealed security cap screws	Concealed security cap screws	Concealed security cap screws	Concealed security cap screws

KEY FEATURES:

- Stylish and customisable
- Robust, vandal and weather resistant
- Surface or flush mount
- Available in Concentrator, RS-485, VoIP and Direct Dial systems



Concentrator	VSC-1A1	VSC-1A4					
RS 485	VSC-2A1	VSC-2A4		VSC-2B1	VSC-2B4	VMC-2B5	VMC-2BK
VoIP	VSC-3A1	VSC-3A4					
Direct dial			VDC-4BK	VDC-4B1	VDC-4B4		

CONCENTRATOR NETWORKED INTERCOM SYSTEM

- Low cost, current loop, star wired topology
- Cabling distance up to 250m
- Reduced cabling and installation costs
- Crystal clear voice communications
- Connects to the RS-485 networked intercom systems via a concentrator unit
- Up to 8 intercoms can be connected to 1 concentrator unit
- Easily integrates with Security and Building Management Systems, Access Control and CCTV Systems

RS-485 NETWORKED INTERCOM AND PUBLIC ADDRESS SYSTEM

- Expandable up to 8,000 devices
- Crystal clear voice communications
- Long cabling distance (up to 1km)
- Easily integrates with Security and Building Management Systems, Access Control and CCTV Systems

VOICE OVER IP (VoIP) NETWORKED INTERCOM AND PUBLIC ADDRESS SYSTEM

- Expandable and flexible system architecture (limited only by network bandwidth)
- Crystal clear voice communications
- Reduced cabling and installation costs
- Easily integrates with Security and Building Management Systems, Access Control and CCTV Systems
- Connects to standard Ethernet network

DIRECT DIAL INTERCOM SYSTEM

- Programmable call buttons
- Loud speaking, hands-free operation
- 2 relay contact outputs
- 1 remote dial digital input
- DTMF and RS-232 configurable
- Connects to standard PABX and PSTN
- Expandable architecture